

**PRODUCT DATA SHEET**

Zoom Mini 900lm 827 5-60° 15W 3-circuit WH

Art.no: 7060-560-3

*Lighting Solutions*

Zoom Mini 900lm 827 5-60° 15W 3-circuit WH

**A⁺⁺**

Zoom Mini is relatively small spotlight for use in track lighting systems. The unique zoom patent makes it possible to vary the beam angel between 5 - and 60 degrees making this model highly versatile. The Zoom Mini is available in both 2700 – and 3000 Kelvin and is made from robust die-cast aluminum. Choose between on/off, phase cut and DALI dimming.

ELECTRICAL DATA

Protection Class (system)	1
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA

IP (system)	IP20
Outdoor	No

PHOTOMETRIC DATA

Efficacy (system) (lm/W)	34
--------------------------	----

**PRODUCT DATA SHEET**

Zoom Mini 900lm 827 5-60° 15W 3-circuit WH

Art.no: 7060-560-3

*Lighting Solutions*

PHOTOMETRIC DATA	
CRI / Ra ($\geq$)	80
CCT (Color Temperature) (K)	2700
Color Code	827
Lightsource Type	LED (built in)
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 100 000
UGR ($\leq$)	18
Manufacturer (light source)	Cree

DRIVER	
CC (driver) [mA]	null - null
CC (forward voltage driver) (V)	null - null

DIMENSIONS	
Length (product) (mm)	261.0
Width (product) (mm)	60.0
Weight (product) (kg)	0.95

MATERIALS AND SURFACES	
Color	White

INSTALLATION AND CONNECTION	
Areas of use	Hotel, Museum, Office, Shop, Showroom
Mounting	Track, Ceiling
Connection (system)	Track 3-Circuit

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A++

ALTERNATIVE DRIVERS	
Current Setting Existing Driver	250 - 100



PRODUCT DATA SHEET

Zoom Mini 900lm 827 5-60° 15W 3-circuit WH

Art.no: 7060-560-3



Lighting Solutions

LIGHT DISTRIBUTION

