

**PRODUCT DATA SHEET**

Zoom Mini 1250lm 927 5-60° 15W 3-circuit BK Phasecut

Art.no: 7063-02-560-2

*Lighting Solutions*

## Zoom Mini 1250lm 927 5-60° 15W 3-circuit BK Phasecut



Zoom Mini is relatively small spotlight for use in track lighting systems. The unique zoom patent makes it possible to vary the beam angle between 5 - and 60 degrees making this model highly versatile. This Zoom Mini variant is available in both black and white color, 2700 – and 3000 Kelvin and with phase cut dimming. The spotlight is made from robust die-cast aluminum.

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	Phase-Cut
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No

**PRODUCT DATA SHEET**

Zoom Mini 1250lm 927 5-60° 15W 3-circuit BK Phasecut

Art.no: 7063-02-560-2

*Lighting Solutions*

PHOTOMETRIC DATA	
CRI / Ra (>=)	90
CCT (Color Temperature) (K)	2700
Color Code	927
Lightsource Type	LED (built in)
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 100 000
Manufacturer (light source)	Bridgelux

DRIVER	
Protection Class (driver)	1
Dimming (driver)	Phase-Cut
Dimming Minimum Level (%)	1.0
Dimming Phasecut Type	Leading / Trailing edge
IP (driver)	IP20
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	350 - null
CC (forward voltage driver) (V)	21.0 - 42.0
Max load pr circuit - B10	35
Max load pr circuit - B16	56
Max load pr circuit - C10	74
Max load pr circuit - C16	118

DIMENSIONS	
Length (product) (mm)	261.0
Width (product) (mm)	60.0
Weight (product) (kg)	0.95

MATERIALS AND SURFACES	
Color	Black

INSTALLATION AND CONNECTION	
Areas of use	Hotel, Museum, Office, Shop, Showroom
Mounting	Track, Ceiling
Connection (system)	Track 3-Circuit



## PRODUCT DATA SHEET

Zoom Mini 1250lm 927 5-60° 15W 3-circuit BK Phasecut  
Art.no: 7063-02-560-2



*Lighting Solutions*

### ENERGY AND CERTIFICATIONS

CE mark	Yes
Energy Efficiency Class	F

### ALTERNATIVE DRIVERS

Current Setting Existing Driver	250 - 100
---------------------------------	-----------

### LIGHT DISTRIBUTION

