

**PRODUCT DATA SHEET**

Zoom Mini 1300lm 930 5-60° 15W 3-circuit BK Phasecut

Art.no: 7064-02-560-2

*Lighting Solutions*

## Zoom Mini 1300lm 930 5-60° 15W 3-circuit BK Phasecut



Zoom Mini is relatively small spotlight for use in track lighting systems. The unique zoom patent makes it possible to vary the beam angel between 5 - and 60 degrees making this model highly versatile. This Zoom Mini variant is available in both black and white color, 2700 – and 3000 Kelvin and with phase cut dimming. The spotlight is made from robust die-cast aluminum.

**ELECTRICAL DATA**

|                           |           |
|---------------------------|-----------|
| Protection Class (system) | 1         |
| Dimming (system)          | Phase-Cut |
| Voltage (system) [V]      | 230V 50Hz |

**TECHNICAL DATA**

|             |      |
|-------------|------|
| IP (system) | IP20 |
| Outdoor     | No   |

**PRODUCT DATA SHEET**

Zoom Mini 1300lm 930 5-60° 15W 3-circuit BK Phasecut

Art.no: 7064-02-560-2

*Lighting Solutions*

| PHOTOMETRIC DATA            |                 |
|-----------------------------|-----------------|
| CRI / Ra ( $\geq$ )         | 90              |
| CCT (Color Temperature) (K) | 3000            |
| Color Code                  | 930             |
| Lightsource Type            | LED (built in)  |
| Lens (Diffuser)             | Clear           |
| Lifetime (h)                | L80B10: 100 000 |
| Manufacturer (light source) | Bridgelux       |

| DRIVER                                 |                         |
|----------------------------------------|-------------------------|
| Protection Class (driver)              | 2                       |
| Dimming (driver)                       | Phase-Cut               |
| Dimming Minimum Level (%)              | 1.0                     |
| Dimming Phasecut Type                  | Leading / Trailing edge |
| IP (driver)                            | IP20                    |
| Constant current or voltage (CC or CV) | CC                      |
| CC (driver) [mA]                       | 350 - null              |
| CC (forward voltage driver) (V)        | 21.0 - 42.0             |
| Max load pr circuit - B10              | 35                      |
| Max load pr circuit - B16              | 56                      |
| Max load pr circuit - C10              | 74                      |
| Max load pr circuit - C16              | 118                     |

| DIMENSIONS            |       |
|-----------------------|-------|
| Length (product) (mm) | 261.0 |
| Width (product) (mm)  | 60.0  |
| Weight (product) (kg) | 0.95  |

| MATERIALS AND SURFACES |       |
|------------------------|-------|
| Color                  | Black |

| INSTALLATION AND CONNECTION |                                       |
|-----------------------------|---------------------------------------|
| Areas of use                | Hotel, Museum, Office, Shop, Showroom |
| Mounting                    | Track, Ceiling                        |
| Connection (system)         | Track 3-Circuit                       |



## PRODUCT DATA SHEET

Zoom Mini 1300lm 930 5-60° 15W 3-circuit BK Phasecut

Art.no: 7064-02-560-2



*Lighting Solutions*

### ENERGY AND CERTIFICATIONS

|                         |     |
|-------------------------|-----|
| CE mark                 | Yes |
| Energy Efficiency Class | A++ |

### ALTERNATIVE DRIVERS

|                                 |           |
|---------------------------------|-----------|
| Current Setting Existing Driver | 250 - 100 |
|---------------------------------|-----------|

### LIGHT DISTRIBUTION

