

**PRODUCT DATA SHEET**

Zoom Mini 900lm 927 CRI97 5-60° 15W 1-circuit BK Phasecut

Art.no: 7066-02-560-2

*Lighting Solutions*

Zoom Mini 900lm 927 CRI97 5-60° 15W 1-circuit BK Phasecut



Zoom Mini is relatively small spotlight for use in track lighting systems. The unique zoom patent makes it possible to vary the beam angle between 5 - and 60 degrees making this model highly versatile. This Zoom Mini variant is available in both black and white color, 2700 – and 3000 Kelvin and with phase cut dimming. The spotlight is made from robust die-cast aluminum.

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	Phase-Cut
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No

**PRODUCT DATA SHEET**

Zoom Mini 900lm 927 CRI97 5-60° 15W 1-circuit BK Phasecut

Art.no: 7066-02-560-2

*Lighting Solutions*

PHOTOMETRIC DATA	
CRI / Ra (>=)	97
CCT (Color Temperature) (K)	2700
Color Code	927
Lightsource Type	LED (built in)
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 100 000
Manufacturer (light source)	Cree

DRIVER	
Manufacturer (driver)	AcTEC
Protection Class (driver)	2
Max Output Voltage (V)	37
Dimming Minimum Level (%)	1.0
Dimming Phasecut Type	Leading / Trailing edge
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	350 - null
CC (forward voltage driver) (V)	14.0 - 29.0
Output Current Tolerance (%)	5.0
Max load pr circuit - B10	140
Max load pr circuit - B16	224
Max load pr circuit - C10	142
Max load pr circuit - C16	228
Inrush current time (µs)	100.0
Inrush current I _{max} (A)	5.0

DIMENSIONS	
Length (product) (mm)	261.0
Width (product) (mm)	60.0
Weight (product) (kg)	0.95

MATERIALS AND SURFACES	
Color	Black

**PRODUCT DATA SHEET**

Zoom Mini 900lm 927 CRI97 5-60° 15W 1-circuit BK Phasecut

Art.no: 7066-02-560-2

*Lighting Solutions*

INSTALLATION AND CONNECTION	
Areas of use	Hotel, Museum, Office, Shop, Showroom
Mounting	Track, Ceiling
Connection (system)	Track 1-Circuit

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A++

ALTERNATIVE DRIVERS	
Current Setting Existing Driver	250 - 100

LIGHT DISTRIBUTION