

**PRODUCT DATA SHEET**

Zoom Mini 900lm 930 CRI97 5-60° 15W 1-circuit BK Phasecut

Art.no: 7067-560-2

*Lighting Solutions*

Zoom Mini 900lm 930 CRI97 5-60° 15W 1-circuit BK Phasecut



Zoom Mini is relatively small spotlight for use in track lighting systems. The unique zoom patent makes it possible to vary the beam angle between 5 - and 60 degrees making this model highly versatile. This Zoom Mini variant is available in both black and white color, 2700 – and 3000 Kelvin and with phase cut dimming. The spotlight is made from robust die-cast aluminum.

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	Phase-Cut
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No

**PRODUCT DATA SHEET**

Zoom Mini 900lm 930 CRI97 5-60° 15W 1-circuit BK Phasecut

Art.no: 7067-560-2

*Lighting Solutions*

PHOTOMETRIC DATA	
CRI / Ra (>=)	97
CCT (Color Temperature) (K)	3000
Color Code	930
Lightsource Type	LED (built in)
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 100 000
Manufacturer (light source)	Cree

DRIVER	
CC (driver) [mA]	null - null
CC (forward voltage driver) (V)	null - null

DIMENSIONS	
Length (product) (mm)	261.0
Width (product) (mm)	60.0
Weight (product) (kg)	0.95

MATERIALS AND SURFACES	
Color	Black

INSTALLATION AND CONNECTION	
Areas of use	Hotel, Museum, Office, Shop, Showroom
Mounting	Track, Ceiling
Connection (system)	Track 1-Circuit

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A++

ALTERNATIVE DRIVERS	
Current Setting Existing Driver	250 - 100



PRODUCT DATA SHEET

Zoom Mini 900lm 930 CRI97 5-60° 15W 1-circuit BK Phasecut

Art.no: 7067-560-2



Lighting Solutions

LIGHT DISTRIBUTION

