

**PRODUCT DATA SHEET**

Aria LED 88W 740 Asym Ø60 IP66 Alu 6m 2.5mm2 kabel (Gen1)

Art.no: 729-04-1

*Lighting Solutions*

Aria LED 88W 740 Asym Ø60 IP66 Alu 6m 2.5mm2 kabel (Gen1)



Aria is a LED luminaire for post mounting. We have developed this luminaire with an asymmetrical reflector giving beam angle of 60x120 degrees. Aria has a fixation of Ø60mm. The luminaire has an IP66 classification and this guarantees that it will withstand very demanding conditions. The Aria is available in several different models

ELECTRICAL DATA	
Protection Class (system)	2
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP66
Outdoor	Yes

PHOTOMETRIC DATA	
CRI / Ra (>=)	70

**PRODUCT DATA SHEET**Aria LED 88W 740 Asym Ø60 IP66 Alu 6m 2.5mm² kabel (Gen1)

Art.no: 729-04-1

*Lighting Solutions*

PHOTOMETRIC DATA	
CCT (Color Temperature) (K)	4000
Color Code	740
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lens (Diffuser)	Clear

DRIVER	
Manufacturer (driver)	TCI
Max Output Voltage (V)	390
Dimming (driver)	None
IP (driver)	IP20
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	200 - 350
Current setting (driver)	DIP-switch
CC (forward voltage driver) (V)	30.0 - 270.0
Output Current Tolerance (%)	5.0
Current Ripple (%)	3.0
Max load pr circuit - B10	18
Max load pr circuit - B16	30
Max load pr circuit - C10	28
Max load pr circuit - C16	46
Inrush current time (µs)	100.0
Inrush current I _{max} (A)	45.0

DIMENSIONS	
Length (product) (mm)	390.0
Width (product) (mm)	215.0
Height (product) (mm)	715.0
Weight (product) (kg)	14.05

MATERIALS AND SURFACES	
Color	Aluminium
Corrosion Class	C3

**PRODUCT DATA SHEET**Aria LED 88W 740 Asym Ø60 IP66 Alu 6m 2.5mm² kabel (Gen1)

Art.no: 729-04-1

*Lighting Solutions***INSTALLATION AND CONNECTION**

Connection (system)	Cable 6m
---------------------	----------

ENERGY AND CERTIFICATIONS

CE mark	Yes
Energy Efficiency Class	A++ - A

ALTERNATIVE DRIVERS

Current Setting Existing Driver	200 - 350
---------------------------------	-----------