


**PRODUCT DATA SHEET**

Pavo P 2090lm 830 22W EMG3 ST ø410mm IP44 WH

Art.no: 8017646

*Lighting Solutions*

L, mm	W, mm	A, mm	B, mm	C, mm
280	95	135	87	77.5
360	105	196	104	123
410	115	239	157	149.5
500	140	317	191.5	124.5

Pavo P 2090lm 830 22W EMG3 ST ø410mm IP44 WH



Surface mounted LED plafond with direct light distribution. Opal PMMA diffuser and steel housing. UGR index: <=22. IP44. IK02. 3 hours emergency with Selftest.

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	None
Voltage (system) [V]	230V 50Hz
Emergency light (h)	3 hours
Emergency light testing	Selftest

TECHNICAL DATA	
IK (system)	IK02
IP (system)	IP44
Outdoor	No
Operating temperature (°C)	-15 - 35

**PRODUCT DATA SHEET**

Pavo P 2090lm 830 22W EMG3 ST ø410mm IP44 WH

Art.no: 8017646

*Lighting Solutions*

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	95
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	3000
Color Code	830
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lens (Diffuser)	Opal
Lifetime (h)	L70B50: 40 000
MacAdam (SDCM)	5
UGR (<=)	22

DIMENSIONS	
Length (product) (mm)	410.0
Width (product) (mm)	410.0
Height (product) (mm)	115.0
Weight (product) (kg)	0.9

MATERIALS AND SURFACES	
Color	White
RAL Code	RAL9003

INSTALLATION AND CONNECTION	
Areas of use	Bathroom, Hotel, Office, Open access areas, School, Staircase
Mounting	Surface, Wall, Ceiling
Connection (system)	Terminal

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A+



PRODUCT DATA SHEET

Pavo P 2090lm 830 22W EMG3 ST ø410mm IP44 WH

Art.no: 8017646



Lighting Solutions

LIGHT DISTRIBUTION

