




PRODUCT DATA SHEET

Book Pole-Top Maxi 840 1x36W Ø60mm adapter RAL7016 5m cable

Art.no: 803002



Lighting Solutions



Book Pole-Top Maxi 840 1x36W Ø60mm adapter RAL7016 5m cable



This square pole-top mounted floodlight is designed for outdoor installation on poles with diameters of either 60 mm. Constructed from phospho-chromatised and polyester powder-coated die-cast copper-free aluminum, it ensures durability and resilience against outdoor conditions. The floodlight features tempered safety glass, a moulded silicone gasket, and stainless steel screws for added protection. Included is a versatile flange suitable for pole diameters of 60 mm or 76 mm, providing flexibility in installation. The illumination is powered by 12 or 24 CREE XP-G2 LEDs known for their efficiency and brightness. The built-in LED driver operates on 220-240V and 50-60Hz, streamlining the installation process. With an IP65 rating, this floodlight offers high-level protection against dust and water, making it ideal for diverse outdoor applications, such as lighting up parking lots, pathways, or any outdoor space requiring effective illumination.

ELECTRICAL DATA	
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP65

**PRODUCT DATA SHEET**

Book Pole-Top Maxi 840 1x36W Ø60mm adapter RAL7016 5m cable
Art.no: 803002



Lighting Solutions

PHOTOMETRIC DATA	
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	4000
Color Code	840

DIMENSIONS	
Length (product) (mm)	445.0
Width (product) (mm)	212.0
Height (product) (mm)	43.0
Weight (product) (kg)	3.0

MATERIALS AND SURFACES	
Color	Dark Grey
RAL Code	RAL7016

INSTALLATION AND CONNECTION	
Areas of use	Outdoor, Parking, Street
Mounting	Mast
Connection (system)	Cable 5m