NORLUX®

Lighting Solutions

Ledline 2750lm 830 Opal 25W L:1200mm WH

CE ☐ 230V 50Hz IP40 ⌂ A++ - A

LEDline is a modern linear LED system for seamless lighting. It is based on modular chassis details allowing for seamless extensions through both straight connectors, 90 degrees corners and X-crosses. This allows light designers to make tailor fit lighting systems in an easy manner. The chassis details assure easy installation without failures. Add 1 pc 8050-05 for each mains supply (each row or standalone). Also add mounting accessories.

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP40
Outdoor	No

PHOTOMETRIC DATA

CRI / Ra (>=)	80
CCT (Color Temperature) (K)	3000
Color Code	830
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lens (Diffuser)	Opal
Lifetime (h)	L80B10: 100 000

DIMENSIONS

Width (product) (mm)	56.0
Heigth (product) (mm)	84.0

MATERIALS AND SURFACES

Color	White

INSTALLATION AND CONNECTION

Areas of use	Generally, Industrial, Shop
Mounting	Recessed, Surface, Ceiling, Pendant
Connection (system)	LEDLine 5-pin

ENERGY AND CERTIFICATIONS

CE mark	Yes
Energy Efficiency Class	A++ - A