

**PRODUCT DATA SHEET**

Ledline 9200lm 840 Opal 75W L:2400mm GR

Art.no: 805014-02-1

*Lighting Solutions*

## Ledline 9200lm 840 Opal 75W L:2400mm GR



LEDline is a modern linear LED system for seamless lighting. It is based on modular chassis details allowing for seamless extensions through both straight connectors, 90 degrees corners and X-crosses. This allows light designers to make tailor fit lighting systems in an easy manner. The chassis details assure easy installation without failures. Add 1 pc 8050-05 for each mains supply (each row or standalone). Also add mounting accessories.

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP40
Outdoor	No

PHOTOMETRIC DATA	
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	3000
Color Code	830
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lens (Diffuser)	Opal
Lifetime (h)	L80B10: 100 000

DRIVER	
Manufacturer (driver)	Lifud
Protection Class (driver)	1
Max Output Voltage (V)	55

**PRODUCT DATA SHEET**

Ledline 9200lm 840 Opal 75W L:2400mm GR

Art.no: 805014-02-1

*Lighting Solutions*

<b>DRIVER</b>	
IP (driver)	IP20
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	900 - null
CC (forward voltage driver) (V)	33.0 - 42.0
Output Current Tolerance (%)	5.0
Max load pr circuit - B10	5
Max load pr circuit - B16	8
Max load pr circuit - C10	8
Max load pr circuit - C16	14
Max load pr circuit - C20	17
Max load pr circuit - C25	22
Leakage current (mA)	10.0
Inrush current time ( $\mu$ s)	350.0
Inrush current I <sub>max</sub> (A)	120.0

<b>DIMENSIONS</b>	
Width (product) (mm)	56.0
Height (product) (mm)	84.0

<b>INSTALLATION AND CONNECTION</b>	
Areas of use	Generally, Industrial, Shop
Mounting	Recessed, Surface, Ceiling, Pendant
Connection (system)	LEDLine 5-pin

<b>ENERGY AND CERTIFICATIONS</b>	
CE mark	Yes
Energy Efficiency Class	A++ - A