

**PRODUCT DATA SHEET**

Galactic C 4200lm 927/930 Prism Ø400 40W BK Up/Down
Art.no: 9057-4-02-2



Lighting Solutions



Galactic C 4200lm 927/930 Prism Ø400 40W BK Up/Down



Galactic C is our new series of circular lamps. Modern design combined with prismatic diffuser that gives a pleasant and comfortable light. Galactic has several mounting options, recessed, semi-recessed, surface mounted or suspended. Choose between 2700K and 3000K (dip-switch) with dircet light or direct / indirect light. Galactic is delivered in size: Ø400mm, Ø600mm, Ø800mm and 1000mm.

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK03
IP (system)	IP40
Outdoor	No
Operating temperature (°C)	-20 - 40

**PRODUCT DATA SHEET**

Galactic C 4200lm 927/930 Prism Ø400 40W BK Up/Down

Art.no: 9057-4-02-2

*Lighting Solutions*

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	80
CRI / Ra (>=)	90
CCT (Color Temperature) (K)	2700-3000K
Color Code	927/930
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lens (Diffuser)	Micropris.
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	3
Manufacturer (light source)	Hong Li Zhi Hui Group Co., Ltd

DRIVER	
Manufacturer (driver)	Up-Shine
Standby power Psb (W) <	0.5
Flicker metric (Pst LM) <	1.0
Stroboscopic effect metric (SVM) <	0.4
Max Output Voltage (V)	42
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Flicker-free	Yes
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	500 - 1000
CC (forward voltage driver) (V)	28.0 - 42.0
CV (driver) [V]	40
Output Current Tolerance (%)	5.0
Current Ripple (%)	5.0
Max load pr circuit - B10	10
Max load pr circuit - B16	16
Max load pr circuit - C10	17
Max load pr circuit - C16	27
Max load pr circuit - C20	33
Leakage current (mA)	0.7
Inrush current time (µs)	400.0
Inrush current I _{max} (A)	18.0

**PRODUCT DATA SHEET**

Galactic C 4200lm 927/930 Prism Ø400 40W BK Up/Down

Art.no: 9057-4-02-2

*Lighting Solutions*

DIMENSIONS	
Length (product) (mm)	400.0
Width (product) (mm)	400.0
Height (product) (mm)	102.0
Weight (product) (kg)	3.2
Diameter (product) (mm)	400.0

MATERIALS AND SURFACES	
Color	Black
RAL Code	RAL9005
Corrosion Class	C1
Surface treatment	Powdercoated
Housing Material	Aluminium 6063
Housing Material %	33.0
Diffuser Material	Polycarbonate
Diffuser Material%	3.5000000000000004
Material 2%	48.0
Material 3%	2.5
Material 4%	7.5
Material 5%	2.5
Material 6%	1.0
Material 7%	0.2
Material 8%	0.2
Material 9%	0.5

INSTALLATION AND CONNECTION	
Areas of use	Hotel
Mounting	Partial-recessed, Surface, Pendant
Connection (system)	Terminal

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	F
CE mark	Yes