



PRODUCT DATA SHEET

LED Strip COB 24V 930 720lm/m 8,2W/m IP20 2m cable L=5m

Art.no: DL-101020-24-3000-5



LED Strip COB 24V 930 720lm/m 8,2W/m IP20 2m cable L=5m



The LED Strip COB Short Cut offers perfect, uniform, and comfortable light without visible points or spots, creating an atmosphere that is both inviting and functional. Short distances between each cutting point, with only 13.9 mm per cutting length, provide flexible installation, allowing you to customize the lighting according to your needs and preferences. With 3-step MacAdam color consistency, you can be confident that our light remains stable and uniform over time. Choose between 2700K, 3000K, or 4000K color temperatures. This LED strip has a beam angle of 120° and a CRI of 90, accurately rendering colors in a natural way. Choose between variants with IP20 or IP65 ratings for both indoor and outdoor use.

ELECTRICAL DATA	
Protection Class (system)	3
Dimming (system)	Depending on Driver
Voltage (system) [V]	24VDC
Power pr. meter (W/m)	8.2
Max. power (W)	9.02

**PRODUCT DATA SHEET**

LED Strip COB 24V 930 720lm/m 8,2W/m IP20 2m cable L=5m

Art.no: DL-101020-24-3000-5

*Lighting Solutions*

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Operating temperature (°C)	-20 - 45
Heat sink needed	No

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	87
CRI / Ra (>=)	90
CCT (Color Temperature) (K)	3000
Color Code	930
Lifetime (h)	L80B10: 50.000
MacAdam (SDCM)	3
LED/m	504
Lumen pr. meter (lm/m)	720

DRIVER	
Constant current or voltage (CC or CV)	CV

DIMENSIONS	
Length (product) (mm)	5000.0
Width (product) (mm)	8.0
Weight (product) (kg)	0.065
Max. length (m)	5
Max Width LED Strip (mm)	8.0

INSTALLATION AND CONNECTION	
Connection LED Strip	Cable 2m

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	F
CE mark	Yes
EPD number	NEPD-14535-15052