

**PRODUCT DATA SHEET**

Driver 350-1050mA cc (10-46V) 45W DT8 DALI TW 2-ch 18i5 DALI
 Art.no: IEM45D-TW-01

*Lighting Solutions*

Driver 350-1050mA cc (10-46V) 45W DT8 DALI TW 2-ch 18i5 DALI



ELECTRICAL DATA	
Dimming (system)	DALI2, Push

TECHNICAL DATA	
Outdoor	No

DRIVER	
Manufacturer (driver)	AcTEC
Protection Class (driver)	2
Flicker metric (Pst LM) <	1.0
Stroboscopic effect metric (SVM) <	0.4
Max Output Voltage (V)	59
Dimming (driver)	DALI2, Push
Dimming Minimum Level (%)	2.0
IP (driver)	IP20

**PRODUCT DATA SHEET**

Driver 350-1050mA cc (10-46V) 45W DT8 DALI TW 2-ch 18i5 DALI
Art.no: IEM45D-TW-01



Lighting Solutions

DRIVER	
Expected Lifetime (driver) (h)	50000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	350 - 1050
Current setting (driver)	DIP-switch
CC (forward voltage driver) (V)	10.0 - 50.0
Output Current Tolerance (%)	5.0
Current Ripple (%)	20.0
Max load pr circuit - B10	23
Max load pr circuit - B16	37
Max load pr circuit - C10	46
Max load pr circuit - C16	74
Inrush current time (μ s)	100.0
Inrush current I _{max} (A)	30.0

DIMENSIONS	
Length (product) (mm)	135.0
Width (product) (mm)	24.0
Height (product) (mm)	72.0
Weight (product) (kg)	0.19

MATERIALS AND SURFACES	
Color	White

ENERGY AND CERTIFICATIONS	
CE mark	Yes