

**PRODUCT DATA SHEET**

Driver 24V cv 75W Phasecut IP20 Lifud

Art.no: LF-GAT075-3125-24

*Lighting Solutions*

Driver 24V cv 75W Phasecut IP20 Lifud



Dimmable 24V CV LED-driver 75W. Used on our LED-strips. Phase-Cut. Constant Voltage.

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	Phase-Cut
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Operating temperature (°C)	-20 - 45

DRIVER	
Manufacturer (driver)	Lifud
Protection Class (driver)	2
Max Output Voltage (V)	24

**PRODUCT DATA SHEET**

Driver 24V cv 75W Phasecut IP20 Lifud

Art.no: LF-GAT075-3125-24

*Lighting Solutions*

DRIVER	
Dimming (driver)	Phase-Cut
Dimming Minimum Level (%)	1.0
Dimming Phasecut Type	Leading / Trailing edge
IP (driver)	IP20
Constant current or voltage (CC or CV)	CV
CV (driver) [V]	24
Leakage current (mA)	0.5
Inrush current time (μ s)	300.0
Inrush current I _{max} (A)	50.0

DIMENSIONS	
Length (product) (mm)	300.0
Width (product) (mm)	42.0
Height (product) (mm)	31.0

MATERIALS AND SURFACES	
Color	White