NORLUX®
Lighting Solutions

Ledline

CE ☐ 230V 50Hz IP40 ⌂

A++ - A

LEDline is a modern linear LED system for seamless lighting. It is based on modular chassis details allowing for seamless extensions through both straight connectors, 90 degrees corners and X-crosses. This allows light designers to make tailor fit lighting systems in an easy manner. The chassis details assure easy installation without failures. Add 1 pc 8050-05 for each mains supply (each row or standalone). Also add mounting accessories.

VARIANTS

Art.no.	Effect	Lumen out	CCT	Beam angle	Lens	CRI (>)	Dimming	Length	Color
805004-03-3-ddd	70W	5950 lm	3000K	110	Opal	80		2400.0 mm	White
805004-03-2-ddd	70W	6800 lm	3000K	110	Opal	80	DALI2	2400.0 mm	Black
805003-02-3	50W	4090 lm	3000K	110	Opal	80		1500.0 mm	White
805002-02-3	40W	3650 lm	3000K	110	Opal	80		1200.0 mm	White
805002-02-2	40W	3650 lm	3000K	110	Opal	80		1200.0 mm	Black
805014-02-1			3000K	110	Opal	80			
805002-2-ddd	40W	3650 lm	3000K	110	Opal	80		1200.0 mm	Black
805008-2-ddd	40W	3650 lm	3000K	110	Opal	80		600.0 mm	Black
805008-3-ddd	40W	3650 lm	3000K	110	Opal	80		600.0 mm	White
805010-3			3000K	110	Opal	80			White

NORLUX®
Lighting Solutions

Art.no.	Effect	Lumen out	CCT	Beam angle	Lens	CRI (>)	Dimming	Length	Color
805001-3			3000K	110	Opal	80			White
805006-3	40W	3650 lm	3000K	110	Opal	80		600.0 mm	White
805003-3-ddd	50W	4090 lm	3000K	110	Opal	80		1500.0 mm	White
805002-3-ddd	40W	3650 lm	3000K	110	Opal	80		1200.0 mm	White
805005-3-ddd	40W	3650 lm	3000K	110	Opal	80		600.0 mm	White
805006-3-ddd	40W	3650 lm	3000K	110	Opal	80		600.0 mm	White
805005-3	40W	3650 lm	3000K	110	Opal	80		600.0 mm	White