

**PRODUCT DATA SHEET**

Leila

Art.no: Leila-Base

*Lighting Solutions*

Leila



This bestseller has quickly become an industry standard within recessed general lighting. Leila is designed with opal diffuser and reflector, this ensures high lumen output with no glare.

ELECTRICAL DATA	
Forward Current LED (mA)	600
Power (system) (W)	25
Protection Class (system)	2
Dimming (system)	Ingen
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
Velg annen produktarkmal	1 [Downlights]
Product Family	Leila
IP (system)	IP20
Cut-out (mm)	Ø190
Outdoor	No

**PRODUCT DATA SHEET**

Leila

Art.no: Leila-Base

*Lighting Solutions*

PHOTOMETRIC DATA	
Lightsource Type	LED (innebygget)
Lens (Diffuser)	Opal
Lifetime (h)	L80B10: 100 000
UGR (<=)	22

DRIVER	
CC (driver) [mA]	null - null
CC (forward voltage driver) (V)	null - null

DIMENSIONS	
Height (product) (mm)	108.0
Width (product) (mm)	202.0
Weight (product) (kg)	1.15

INSTALLATION AND CONNECTION	
Mounting	Innfelt, Tak
Areas of use	Generelt, Kontor, Butikk

ENERGY AND CERTIFICATIONS	
Energy Efficiency Class	A++ - A
CE mark	Yes

ALTERNATIVE DRIVERS	
Alternative DALI Driver 1	28000676 + 28001116 - Driver 500-1400mA cc LCA 45W 500-1400mA one4All SC PRE DALI + Plug 600mA
Alternative DALI Driver 2	LCM-25DA - Driver 350/500/600/700/900/1050mA cc 25W DALI MeanWell
Alternative DALI Driver 3	LCM-40D - Driver 350/500/600/700/900/1050mA cc 40W DALI MeanWell