

**PRODUCT DATA SHEET**

Tony Pendant G3 927 9,3W Ø:60x250mm 3m BK/GD Phasecut  
Art.no: P-3-0001-2



*Lighting Solutions*



## Tony Pendant G3 927 9,3W Ø:60x250mm 3m BK/GD Phasecut



ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	Phase-Cut
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	90
CRI / Ra (>=)	90

**PRODUCT DATA SHEET**

Tony Pendant G3 927 9,3W Ø:60x250mm 3m BK/GD Phasecut  
Art.no: P-3-0001-2



*Lighting Solutions*

PHOTOMETRIC DATA	
CCT (Color Temperature) (K)	2700
Color Code	927
Lightsource Type	LED (built in)
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 100 000

DRIVER	
Manufacturer (driver)	AcTEC
Protection Class (driver)	2
Max Output Voltage (V)	26
Dimming (driver)	Phase-Cut
Dimming Minimum Level (%)	1.0
Dimming Phasecut Type	Trailing edge
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	500 - null
Current setting (driver)	None
CC (forward voltage driver) (V)	10.0 - 20.0
Output Current Tolerance (%)	5.0
Current Ripple (%)	10.0
Max load pr circuit - B10	125
Max load pr circuit - B16	200
Max load pr circuit - C10	125
Max load pr circuit - C16	200
Inrush current time (µs)	100.0
Inrush current I <sub>max</sub> (A)	5.0

DIMENSIONS	
Width (product) (mm)	60.0
Height (product) (mm)	250.0
Weight (product) (kg)	0.85

MATERIALS AND SURFACES	
Color	Black



**PRODUCT DATA SHEET**

Tony Pendant G3 927 9,3W Ø:60x250mm 3m BK/GD Phasecut

Art.no: P-3-0001-2



*Lighting Solutions*

INSTALLATION AND CONNECTION	
Areas of use	Cottage, Hotel, Residence
Mounting	Ceiling, Pendant
Connection (system)	Cable 3m

ENERGY AND CERTIFICATIONS	
CE mark	Yes