NORLUX®

Lighting Solutions

LED Strip 24Vdc 940 1320lm/m 14,4w/m IP20 2m cable L=5m

CE ◇III◇ 24V IP20

A++ – A

ELECTRICAL DATA	
Protection Class (system)	3
Dimming (system)	Depending on Driver
Voltage (system) [V]	24VDC
Power pr. meter (W/m)	14.4
Max. power (W)	14.4

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Operating temperature (°C)	-20 - 50
Heat sink needed	No

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	92
CRI / Ra (>=)	90
CCT (Color Temperature) (K)	4000
Color Code	940
MacAdam (SDCM)	3
LED Chip	2835
LED/m	60
Lumen pr. meter (lm/m)	1320

DRIVER	
Constant current or voltage (CC or CV)	CV
Inrush current time (µs)	200.0
Inrush current Imax (A)	25.0

DIMENSIONS	
Length (product) (mm)	5000.0
Width (product) (mm)	10.0
Weight (product) (kg)	0.15
Max. length (m)	5
Max Width LED Strip (mm)	11.0

INSTALLATION AND CONNECTION	
LED Strip Mounting	Adhesive tape
Connection LED Strip	Cable 2m

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A++ - A