

**FAMILY PRODUCT SHEET**

Zoom Mini Spotlight

Art.no: Zoom-Mini-Base

*Lighting Solutions*

Zoom Mini Spotlight



Zoom Mini is relatively small spotlight for use in track lighting systems. The unique zoom patent makes it possible to vary the beam angle between 5 - and 60 degrees making this model highly versatile. The Zoom Mini is available in both 2700 – and 3000 Kelvin and is made from robust die-cast aluminum. Choose between on/off, phase cut and DALI dimming.

VARIANTS

Art.no.	Effect	Lumen out	CCT	Beam angle	Lens	CRI (>)	Dimming	Connection	Color
7066-02-560-2	15W		2700K	5-60°	Clear	97		Skinne 1-Tenning	Black
7066-02-560-3	15W		2700K	5-60°	Clear	97		Skinne 1-Tenning	White
7064-02-560-3	15W		3000K	5-60°	Clear	90	Phase-Cut	Skinne 3-Tenning	White
7067-560-2	15W		3000K	5-60°	Clear	97		Skinne 1-Tenning	Black
7063-02-560-3	15W	687 lm	2700K	5-60°	Clear	90	Phase-Cut	Skinne 3-Tenning	White
7063-02-560-2	15W		2700K	5-60°	Clear	90	Phase-Cut	Skinne 3-Tenning	Black
7064-02-560-2	15W		3000K	5-60°	Clear	90	Phase-Cut	Skinne 3-	Black



FAMILY PRODUCT SHEET
Zoom Mini Spotlight
Art.no: Zoom-Mini-Base



Lighting Solutions

Art.no.	Effect	Lumen out	CCT	Beam angle	Lens	CRI (>)	Dimming	Connection	Color
								Tenning	
7066-560-3	15W	687 lm	2700K	5-60°	Clear	97		Skinne 1-Tenning	White
7060-560-2	15W	511-275 lm	2700K	5-60	Clear	80		Skinne 3-Tenning	Black
7060-560-3	15W	511-276 lm	2700K	5-60	Clear	80		Skinne 3-Tenning	White
7063-02-560-3-ddd	15W		2700K	5°-60°	Clear	90	DALI2	Skinne 3-Tenning	White
7063-02-560-2-ddd	15W		2700K	5°-60°	Clear	90	DALI2	Skinne 3-Tenning	Black