



**PRODUCT FAMILY SHEET**  
Zoom Mini Spotlight



# Zoom Mini Spotlight

Zoom Mini is relatively small spotlight for use in track lighting systems. The unique zoom patent makes it possible to vary the beam angle between 5- and 60 degrees making this model highly versatile. The Zoom Mini is available in both 2700 and 3000 Kelvin and is made from robust die-cast aluminum. Choose between on/off, phase cut and DALI dimming.

## VERSIONS

Art.No	Effect [W]	Cold Lumen [lm]	Lumen Output [lm]	CCT [K]	Beam Angle [°]	Lens Difuser	CRI [>]	Color	Light Control	Connection
7066-02-560-2	15	900		2700	5-60°	Clear	97	Black	Phase-Cut	Track 1-Circuit
7066-02-560-3	15	900		2700	5-60°	Clear	97	White	Phase-Cut	Track 1-Circuit
7064-02-560-3	15	1300		3000	5-60°	Clear	90	White	Phase-Cut	Track 3-Circuit
7067-560-2	15	900		3000	5-60°	Clear	97	Black	Phase-Cut	Track 1-Circuit
7063-02-560-3	15	1250	687	2700	5-60°	Clear	90	White	Phase-Cut	Track 3-Circuit
7063-02-560-2	15	1250		2700	5-60°	Clear	90	Black	Phase-Cut	Track 3-Circuit
7064-02-560-2	15	1300		3000	5-60°	Clear	90	Black	Phase-Cut	Track 3-Circuit
7060-560-2	15	900	511-275	2700	5-60	Clear	80	Black	None	Track 3-Circuit
7060-560-3	15	900	511-276	2700	5-60	Clear	80	White	None	Track 3-Circuit
7063-02-560-3-ddd	15	1250		2700	5°-60°	Clear	90	White	DALI2	Track 3-Circuit
7063-02-560-2-ddd	15	1250		2700	5°-60°	Clear	90	Black	DALI2	Track 3-Circuit