

**PRODUCT DATA SHEET**

Driver On/Off 900mA Panel max 44W 18i3 Male/ EPN0034

Art.no: 0300-2-03

*Lighting Solutions*

Driver On/Off 900mA Panel max 44W 18i3 Male/ EPN0034



ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Connection 1	18i3 male
Connection 2	EPN0034 female

DRIVER	
Manufacturer (driver)	Philips
Protection Class (driver)	2

**PRODUCT DATA SHEET**

Driver On/Off 900mA Panel max 44W 18i3 Male/ EPN0034

Art.no: 0300-2-03

*Lighting Solutions*

DRIVER	
Standby power P_{sb} (W) <	0.5
Flicker metric (P_{st} LM) <	0.06
Stroboscopic effect metric (SVM) <	0.07
Max Output Voltage (V)	60
Dimming (driver)	None
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	900 - 1050
Current setting (driver)	DIP-switch
CC (forward voltage driver) (V)	30.0 - 42.0
Output Current Tolerance (%)	8.0
Current Ripple (%)	1.0
Max load pr circuit - B10	32
Max load pr circuit - B16	40
Max load pr circuit - C10	42
Max load pr circuit - C16	56
Max load pr circuit - C20	83
Max load pr circuit - C25	104
Max load pr circuit - C32	136
Leakage current (mA)	0.7
Inrush current time (μ s)	258.0
Inrush current I_{max} (A)	19.5

ENERGY AND CERTIFICATIONS	
CE mark	Yes