

**PRODUKTDATABLAD**

Driver On/Off 900mA Panel max 44W 18i3 Male/ EPN0034

Art.no: 0300-2-03

*Lighting Solutions*

Driver On/Off 900mA Panel max 44W 18i3 Male/ EPN0034



ELEKTRISKE DATA	
Beskyttelsesklasse	2
Dimmefunksjon (system)	Ingen
Spenning (V)	230V 50Hz

TEKNISK DATA	
IP (system)	IP20
Utendørs	No
Tilkobling Kabel 1	18i3 hann
Tilkobling Kabel 2	EPN0034 hunn

DRIVER / BALLAST	
Produsent (driver)	Philips
Produsentens driverbeskrivelse	Xitanium 44W 0.9-1.05A 42V DS I 230V

**PRODUKTDATABLAD**

Driver On/Off 900mA Panel max 44W 18i3 Male/ EPN0034

Art.no: 0300-2-03

*Lighting Solutions*

DRIVER / BALLAST	
Effekt (driver) (W)	44
Beskyttelsesklasse (driver)	2
Standbyeffekt Psb (W) <	0.5
Flimmerindikator (Pst LM) <	0.06
Stroboskopeffektindikator (SVM) <	0.07
Maks utgangsspenning (V)	60
Dimmefunksjon (driver)	Ingen
IP-klasse (driver)	IP20
Forventet levetid (driver) (t)	50000
Konstant strøm eller spenning (CC eller CV)	CC
Konstant strøm (CC driver) (mA)	900 - 1050
Strøminnstilling (driver)	DIP-switch
Konstant strøm (CC driftspenning driver) (V)	30.0 - 42.0
Utgangsstrøm toleranse (%)	8.0
Strømkrusning (%)	1.0
Maks belastning per kurs - B10	32
Maks belastning per kurs - B16	40
Maks belastning per kurs - C10	42
Maks belastning per kurs - C16	56
Maks belastning per kurs - C20	83
Maks belastning per kurs - C25	104
Maks belastning per kurs - C32	136
Lekkasjestrøm (mA)	0.7
Startstrøm tid (μ s)	258.0
Startstrøm I _{max} (A)	19.5

ENERGI OG GODKJENNING	
CE-merke	Yes