Driver Phasecut 500mA max 25W 25-50V 18i3&EPN0034

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	Phase-Cut
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Operating temperature (°C)	-20 - 50
Connection 1	18i3 male
Connection 2	EPN0034 female

DRIVER	
Manufacturer (driver)	AcTEC
Protection Class (driver)	2
Max Output Voltage (V)	50
Dimming Minimum Level (%)	1.0
Dimming Phasecut Type	Leading / Trailing edge
IP (driver)	IP20
Expected Lifetime (driver) (h)	30000
CC (driver) [mA]	500 - null
CC (forward voltage driver) (V)	25.0 - 50.0
Output Current Tolerance (%)	5.0
Current Ripple (%)	50.0
Max load pr circuit - B10	35

DRIVER	
Max load pr circuit - B16	56
Max load pr circuit - C10	74
Max load pr circuit - C16	118
Leakage current (mA)	5.0
Inrush current time (µs)	300.0
Inrush current Imax (A)	5.0

DIMENSIONS	
Length (product) (mm)	120.0
Width (product) (mm)	45.0
Heigth (product) (mm)	28.0
Weight (product) (kg)	0.15

ENERGY AND CERTIFICATIONS	
CE mark	Yes