

**PRODUCT DATA SHEET**

Driver DALI 700mA max 45W 25-64V 18i5 DALI/EPN0034

Art.no: 0300-33

*Lighting Solutions*

Driver DALI 700mA max 45W 25-64V 18i5 DALI/EPN0034



DALI2 og push-dim driver Max 45W Change from 350mA til 900mA with DIP switch (default 700mA) Primary side 18i5 male kobling Secondary side EPN0034 kobling

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	DALI2
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Operating temperature (°C)	-20 - 50
Connection 1	18i5 DALI male
Connection 2	EPN0034 female

**PRODUCT DATA SHEET**

Driver DALI 700mA max 45W 25-64V 18i5 DALI/EPN0034

Art.no: 0300-33

*Lighting Solutions*

DRIVER	
Manufacturer (driver)	AcTEC
Protection Class (driver)	2
Standby power Psb (W) <	0.5
Flicker metric (Pst LM) <	1.0
Stroboscopic effect metric (SVM) <	0.4
Max Output Voltage (V)	80
Dimming (driver)	DALI2
Dimming Minimum Level (%)	1.0
IP (driver)	IP20
Expected Lifetime (driver) (h)	100000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	350 - 1000
CC (forward voltage driver) (V)	25.0 - 70.0
Output Current Tolerance (%)	5.0
Current Ripple (%)	40.0
Max load pr circuit - B10	8
Max load pr circuit - B16	14
Max load pr circuit - C10	18
Max load pr circuit - C16	29
Leakage current (mA)	0.7
Inrush current time (μ s)	300.0
Inrush current I _{max} (A)	20.0

DIMENSIONS	
Length (product) (mm)	140.0
Width (product) (mm)	70.0
Height (product) (mm)	27.0
Weight (product) (kg)	0.25

MATERIALS AND SURFACES	
Color	White

ENERGY AND CERTIFICATIONS	
CE mark	Yes



PRODUCT DATA SHEET

Driver DALI 700mA max 45W 25-64V 18i5 DALI/EPN0034

Art.no: 0300-33



Lighting Solutions