

**PRODUKTDATABLAD**

Driver on/off 700mA 30-18W 18i3 male/EPN0034

Art.no: 0300-47

*Lighting Solutions*

## Driver on/off 700mA 30-18W 18i3 male/EPN0034



ELEKTRISKE DATA	
Beskyttelsesklasse	1 or 2
Dimmefunksjon (system)	Ingen
Spenning (V)	230V 50Hz

TEKNISK DATA	
IP (system)	IP20
Utendørs	No
Tilkobling Kabel 1	18i3 hann
Tilkobling Kabel 2	EPN0034 hunn

DRIVER / BALLAST	
Produsent (driver)	Up-Shine
Effekt (driver) (W)	30-18

**PRODUKTDATABLAD**

Driver on/off 700mA 30-18W 18i3 male/EPN0034

Art.no: 0300-47

*Lighting Solutions*

<b>DRIVER / BALLAST</b>	
Beskyttelsesklasse (driver)	2
Standbyeffekt Psb (W) <	0.5
Flimmerindikator (Pst LM) <	1.0
Stroboskopeffektindikator (SVM) <	0.4
Maks utgangsspenning (V)	40
Dimmefunksjon (driver)	Ingen
IP-klasse (driver)	IP20
Forventet levetid (driver) (t)	50000
Konstant strøm eller spenning (CC eller CV)	CC
Konstant strøm (CC driver) (mA)	450 - 750
Konstant strøm (CC driftspenning driver) (V)	30.0 - 40.0
Konstant spenning (CV driver) (V)	33
Utgangsstrøm toleranse (%)	5.0
Strømkrusning (%)	5.0
Maks belastning per kurs - B10	39
Maks belastning per kurs - B16	63
Maks belastning per kurs - C10	39
Maks belastning per kurs - C16	63
Maks belastning per kurs - C20	78
Lekkasjestrøm (mA)	0.5
Startstrøm tid ( $\mu$ s)	224.0
Startstrøm I <sub>max</sub> (A)	23.2

<b>ENERGI OG GODKJENNING</b>	
CE-merke	Yes