

**PRODUKTDATABLAD**

Driver Phasecut 700mA 30W phasecut 18i3 male/EPN0034

Art.no: 0300-48

*Lighting Solutions*

Driver Phasecut 700mA 30W phasecut 18i3 male/EPN0034



ELEKTRISKE DATA	
Beskyttelsesklasse	1 or 2
Dimmefunksjon (system)	Faseavsnitt
Spenning (V)	230V 50Hz

TEKNISK DATA	
IP (system)	IP20
Utendørs	No
Tilkobling Kabel 1	18i3 hann
Tilkobling Kabel 2	EPN0034 hunn

DRIVER / BALLAST	
Produsent (driver)	Up-Shine
Effekt (driver) (W)	30

**PRODUKTDATABLAD**

Driver Phasecut 700mA 30W phasecut 18i3 male/EPN0034

Art.no: 0300-48

*Lighting Solutions*

DRIVER / BALLAST	
Beskyttelsesklasse (driver)	1 or 2
Flimmerindikator (Pst LM) <	1.0
Stroboskopeffektindikator (SVM) <	0.4
Dimmefunksjon (driver)	Faseavsnitt
IP-klasse (driver)	IP20
Forventet levetid (driver) (t)	50000
Konstant strøm eller spenning (CC eller CV)	CC
Konstant strøm (CC driver) (mA)	340 - 700
Konstant strøm (CC driftspenning driver) (V)	null - null
Maks belastning per kurs - B10	39
Maks belastning per kurs - B16	62
Maks belastning per kurs - C10	39
Maks belastning per kurs - C16	62
Maks belastning per kurs - C20	78
Lekkasjestrøm (mA)	0.7
Startstrøm tid (μ s)	80.0
Startstrøm I _{max} (A)	12.5

ENERGI OG GODKJENNING	
CE-merke	Yes