

**PRODUKTDATABLAD**

Driver Dali 700mA 30W Dali 18i5/EPN0034

Art.no: 0300-49

*Lighting Solutions*

Driver Dali 700mA 30W Dali 18i5/EPN0034



ELEKTRISKE DATA	
Beskyttelsesklasse	1 or 2
Dimmefunksjon (system)	DALI
Spenning (V)	230V 50Hz

TEKNISK DATA	
IP (system)	IP20
Utendørs	No
Tilkobling Kabel 1	18i5 DALI hann
Tilkobling Kabel 2	EPN0034 hunn

DRIVER / BALLAST	
Produsent (driver)	Boke
Effekt (driver) (W)	30

**PRODUKTDATABLAD**

Driver Dali 700mA 30W Dali 18i5/EPN0034

Art.no: 0300-49

*Lighting Solutions*

DRIVER / BALLAST	
Beskyttelsesklasse (driver)	2
Standbyeffekt Psb (W) <	0.5
Flimmerindikator (Pst LM) <	1.0
Stroboskopeffektindikator (SVM) <	0.4
Maks utgangsspenning (V)	42
Dimmefunksjon (driver)	DALI2
Minimum dimmenivå (%)	1.0
Type Dimming	Amplitude Modulation
IP-klasse (driver)	IP20
Forventet levetid (driver) (t)	100000
Konstant strøm eller spenning (CC eller CV)	CC
Konstant strøm (CC driver) (mA)	300 - 750
Konstant strøm (CC driftspenning driver) (V)	6.0 - 42.0
Konstant spenning (CV driver) (V)	33
Utgangsstrøm toleranse (%)	5.0
Strømkrusning (%)	5.0
Maks belastning per kurs - B10	48
Maks belastning per kurs - B16	77
Maks belastning per kurs - C10	48
Maks belastning per kurs - C16	77
Maks belastning per kurs - C20	96
Maks belastning per kurs - C25	120
Lekkasjestrøm (mA)	0.7
Startstrøm tid (μ s)	194.0
Startstrøm I _{max} (A)	6.5

ENERGI OG GODKJENNING	
CE-merke	Yes