

**PRODUCT DATA SHEET**

Driver on/off 680mA max 28W 30-40V 18i3/EPN0034

Art.no: 0300-50

*Lighting Solutions*

Driver on/off 680mA max 28W 30-40V 18i3/EPN0034



ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Connection 1	18i3 male
Connection 2	EPN0034 female

DRIVER	
Manufacturer (driver)	Up-Shine
Protection Class (driver)	2

**PRODUCT DATA SHEET**

Driver on/off 680mA max 28W 30-40V 18i3/EPN0034

Art.no: 0300-50

*Lighting Solutions*

DRIVER	
Standby power P_{sb} (W) <	0.5
Flicker metric (P_{st} LM) <	1.0
Stroboscopic effect metric (SVM) <	0.4
Max Output Voltage (V)	40
Dimming (driver)	None
IP (driver)	IP20
Expected Lifetime (driver) (h)	100000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	646 - 714
CC (forward voltage driver) (V)	30.0 - 40.0
CV (driver) [V]	33
Output Current Tolerance (%)	5.0
Current Ripple (%)	5.0
Max load pr circuit - B10	13
Max load pr circuit - B16	20
Max load pr circuit - C10	21
Max load pr circuit - C16	23
Max load pr circuit - C20	42
Leakage current (mA)	0.5
Inrush current time (μ s)	227.2
Inrush current I_{max} (A)	28.8

ENERGY AND CERTIFICATIONS	
CE mark	Yes