



CBU 1-ch 0-10V/Dali Casambi



The AIMOTION controller controls individual luminaires in the Bluetooth Low Energy Mesh network without the use of gateways, routers, repeaters or extra cabling. Configuration and selection of the appropriate profile for the different operating modes (4xDIM, TW, RGB, RGBW, etc.) is carried out wirelessly via the Casambi App.

ELECTRICAL DATA	
Dimming (system)	DALI, 0-10V, 1-10V
Voltage (system) [V]	230V 50Hz
Frequency (Hz)	50Hz
Max Power (A)	0.6

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Operating temperature (°C)	-20 - 50
Last Level	Yes



PRODUCT DATA SHEET
CBU 1-ch 0-10V/Dali Casambi
Art.no: 1003-ASD



Lighting Solutions

TECHNICAL DATA	
Soft Start	Yes

DIMENSIONS	
Length (product) (mm)	56.5
Width (product) (mm)	22.3
Height (product) (mm)	35.8
Weight (product) (kg)	0.05
Cable Dimension	0,75-1,5 mm ²

MATERIALS AND SURFACES	
Color	White
Housing	II

INSTALLATION AND CONNECTION	
Mounting Dimmer	Electrical box

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Dimmer Standard	EN60669
Energy Efficiency Class	A++ - A