

**PRODUCT DATA SHEET**

Panel R Ø400 w/Spring 3600lm 830 35W Opal WH w/o driver
Art.no: 101271-01-3



Lighting Solutions



Panel R Ø400 w/Spring 3600lm 830 35W Opal WH w/o driver



Panel Round is a luminaire suitable for interior use. It is design and developed to suite several applications, e.g. Recessed, Surface mount and as Pendant. The Panel has an opal diffusor

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	Depending on Driver
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Operating temperature (°C)	-10 - 40

**PRODUCT DATA SHEET**

Panel R Ø400 w/Spring 3600lm 830 35W Opal WH w/o driver

Art.no: 101271-01-3

*Lighting Solutions*

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	98
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	3000
Color Code	830
Lightsource Type	LED (built in)
Lens (Diffuser)	Opal
Lifetime (h)	L80B10: 100 000
Forward Current LED (min-max) (mA)	null - 900
Forward Voltage LED (max tp=25) (V)	38.0
Driftspenning LED (min tp=65) (V)	33.0

DIMENSIONS	
Width (product) (mm)	400.0
Height (product) (mm)	30.0
Weight (product) (kg)	1.62

MATERIALS AND SURFACES	
Color	White
RAL Code	RAL9016

INSTALLATION AND CONNECTION	
Areas of use	School, Shop
Mounting	Recessed, Ceiling
Connection (system)	Depending on driver

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	F
CE mark	Yes
Energy Efficiency Class	A+