

**PRODUKTDATABLAD**

Panel R Ø400 w/Spring 3600lm 830 35W Opal WH w/o driver

Art.no: 101271-01-3

*Lighting Solutions*

## Panel R Ø400 w/Spring 3600lm 830 35W Opal WH w/o driver



Panel Round is a luminaire suitable for interior use. It is design and developed to suite several applications, e.g. Recessed, Surface mount and as Pendant. The Panel has an opal diffusor

ELEKTRISKE DATA	
Beskyttelsesklasse	1
Dimmefunksjon (system)	Avhengig av driver
Spenning (V)	230V 50Hz
Driftspenning LED (mA)	900
Effekt (system) (W)	35
Lyskilde Maks Effekt (W) hvis Sokkel	Ledbuiltin

TEKNISK DATA	
IP (system)	IP20
Utendørs	No

**PRODUKTDATABLAD**

Panel R Ø400 w/Spring 3600lm 830 35W Opal WH w/o driver

Art.no: 101271-01-3

*Lighting Solutions*

TEKNISK DATA	
Hullmål (mm)	360
Driftstemperatur (°C)	-10 - 40

LYSTEKNISKE DATA	
Lumen ut (system) (lm)	3421
Kald lumen (t=25) fra chip (lm)	3500
Effektivitet (system) (lm/W)	98
Fargegjengivelse (CRI / Ra) (>=)	80
Fargetemperatur (CCT) (K)	3000
Fargekode	830
Lyskildetype	LED (innebygget)
Linse (Diffusor)	Opal
Strålevinkel (°)	90°
Levetid (t)	L80B10: 100 000
Driftstrøm LED (min-max) (mA)	null - 900
Driftspenning LED (max tp=25) (V)	38.0
Driftspenning LED (min tp=65) (V)	33.0

DIMENSJONER	
Bredde (produkt) (mm)	400.0
Høyde (produkt) (mm)	30.0
Vekt (produkt) (kg)	1.62

MATERIALER OG OVERFLATER	
Farge	Hvit
RAL Kode	RAL9016

MONTERING OG TILKOBLING	
Bruksområde	Skole, Butikk
Montering	Innfelt, Tak
Tilkobling (system)	Depending on driver

ENERGI OG GODKJENNING	
EPREL Energiklasse	F

**PRODUKTDATABLAD**

Panel R Ø400 w/Spring 3600lm 830 35W Opal WH w/o driver

Art.no: 101271-01-3

*Lighting Solutions*

ENERGI OG GODKJENNING	
CE-merke	Yes
Energy Efficiency Class	A+