




**PRODUCT DATA SHEET**

Plaza Up&amp;Down 900lm 830 15°-210° 10W BK

Art.no: 101510-2

*Lighting Solutions*

## Plaza Up&Down 900lm 830 15°-210° 10W BK



Outdoor luminaire with a modern design with up and down light. Beam angles are adjustable from 15°-210° by changing position of flaps. Made of die-cast aluminum.

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK06
IP (system)	IP65
Outdoor	Yes
Operating temperature (°C)	-20 - 45

**PRODUCT DATA SHEET**

Plaza Up&amp;Down 900lm 830 15°-210° 10W BK

Art.no: 101510-2

*Lighting Solutions*

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	76
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	3000
Color Code	830
Socket / Cap-Base	N/A
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	3

DRIVER	
Manufacturer (driver)	Up-Shine
CC (driver) [mA]	140 - null
CC (forward voltage driver) (V)	80.0 - null
Output Current Tolerance (%)	5.0
Current Ripple (%)	5.0
Max load pr circuit - B10	111
Max load pr circuit - B16	178
Max load pr circuit - C10	111
Max load pr circuit - C16	178
Leakage current (mA)	0.75
Inrush current time (µs)	110.0
Inrush current I <sub>max</sub> (A)	5.76

DIMENSIONS	
Length (product) (mm)	120.0
Width (product) (mm)	96.8
Height (product) (mm)	100.0
Weight (product) (kg)	0.6

MATERIALS AND SURFACES	
Color	Black
RAL Code	RAL9005
Housing Material	Aluminium



**PRODUCT DATA SHEET**

Plaza Up&Down 900lm 830 15°-210° 10W BK

Art.no: 101510-2



*Lighting Solutions*

INSTALLATION AND CONNECTION	
Areas of use	Outdoor
Mounting	Wall
Connection (system)	QuickConnect

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	F
CE mark	Yes

**LIGHT DISTRIBUTION**

