

**PRODUCT DATA SHEET**


Base 5700lm 840 Opal 52W 5x1,5mm2 PG IP66 IK08 L=1541mm DALI
Art.no: 10176083



Lighting Solutions



Base 5700lm 840 Opal 52W 5x1,5mm2 PG IP66 IK08 L=1541mm DALI



Base is a sealed industrial light fixture for ceiling surface mounting, indoor and outdoor (under roof). Base have 5x1,5mm2 PG through-wiring and DALI control. Opal PC (IK08) diffusor. Ask for Chemical agents list to check material resistance. Flexible position of mounting clips, also ready for wire-mount. Easy connection of cable - no tools needed.

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	DALI
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK08
IP (system)	IP66
Operating temperature (°C)	-25 - 35
Through-wiring (mm ²)	5x1,5

**PRODUCT DATA SHEET**

Base 5700lm 840 Opal 52W 5x1,5mm2 PG IP66 IK08 L=1541mm DALI
Art.no: 10176083



Lighting Solutions

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	110
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	4000
Color Code	840
Lightsource Type	LED (built in)
Lens (Diffuser)	PC Opal
Lifetime (h)	L80B50: 70 000

DRIVER	
Max load pr circuit - B10	12
Max load pr circuit - B16	19
Max load pr circuit - C10	20
Max load pr circuit - C16	31
Max load pr circuit - C20	39
Max load pr circuit - C25	49
Inrush current time (μ s)	163.0
Inrush current I _{max} (A)	38.0

DIMENSIONS	
Length (product) (mm)	1541.0
Width (product) (mm)	76.0
Height (product) (mm)	67.0
Weight (product) (kg)	2.0

MATERIALS AND SURFACES	
Color	Grey

INSTALLATION AND CONNECTION	
Areas of use	Generally, Parkinghouse
Mounting	Ceiling
Connection (system)	QuickConnect



PRODUCT DATA SHEET

Base 5700lm 840 Opal 52W 5x1,5mm2 PG IP66 IK08 L=1541mm DALI

Art.no: 10176083



Lighting Solutions

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A++ - A