

**PRODUCT DATA SHEET**

Driver DALI 700mA(250-700) (3-28V) max 20W 18i5 DALI&SM TCI  
Art.no: 151403-700-03



*Lighting Solutions*



## Driver DALI 700mA(250-700) (3-28V) max 20W 18i5 DALI&SM TCI



Preset to 700mA (3-28V)

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	DALI2
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Operating temperature (°C)	-25 - 45
Connection 1	18i5 DALI male
Connection 2	SM Connector

**PRODUCT DATA SHEET**

Driver DALI 700mA(250-700) (3-28V) max 20W 18i5 DALI&SM TCI  
Art.no: 151403-700-03



*Lighting Solutions*

<b>DRIVER</b>	
Manufacturer (driver)	TCI
Max Output Voltage (V)	55
Dimming (driver)	DALI2
Dimming output type	Amplitude Modulation
IP (driver)	IP20
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	250 - 700
Current setting (driver)	DIP-switch
CC (forward voltage driver) (V)	3.0 - 49.0
Current Ripple (%)	3.0
Max load pr circuit - B10	31
Max load pr circuit - B16	50
Max load pr circuit - C10	52
Max load pr circuit - C16	85
Inrush current time ( $\mu$ s)	50.0
Inrush current I <sub>max</sub> (A)	5.0

<b>DIMENSIONS</b>	
Length (product) (mm)	111.0
Width (product) (mm)	52.0
Height (product) (mm)	22.0

<b>ENERGY AND CERTIFICATIONS</b>	
CE mark	Yes