




**PRODUCT DATA SHEET**

Dalim Up or Down 1200lm 40° 20W Dark Grey Phasecut
 Art.no: 2435-40-7

*Lighting Solutions*

Dalim Up or Down 1200lm 40° 20W Dark Grey Phasecut



Dalim are a wall mounted outdoor luminaire. Suited for larger buildings. Quickconnect for easy installation.

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	Phase-Cut
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK08
IP (system)	IP65
Outdoor	Yes
Operating temperature (°C)	-20 - 50

PHOTOMETRIC DATA	
CRI / Ra (>=)	80

**PRODUCT DATA SHEET**

Dalim Up or Down 1200lm 40° 20W Dark Grey Phasecut

Art.no: 2435-40-7

*Lighting Solutions*

PHOTOMETRIC DATA	
CCT (Color Temperature) (K)	3000
Color Code	830
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lens (Diffuser)	Clear
Lifetime (h)	L80: 100 000

DRIVER	
Protection Class (driver)	2
Output Current Tolerance (%)	5.0
Max load pr circuit - B10	12
Max load pr circuit - B16	19
Max load pr circuit - C10	23
Max load pr circuit - C16	39
Leakage current (mA)	0.1
Inrush current time (μ s)	1.7
Inrush current I _{max} (A)	4.1

DIMENSIONS	
Length (product) (mm)	177.0
Width (product) (mm)	140.0
Height (product) (mm)	185.0
Weight (product) (kg)	1.8

MATERIALS AND SURFACES	
Color	Dark Grey
RAL Code	RAL7024
Housing Material	Aluminium

INSTALLATION AND CONNECTION	
Areas of use	Cottage, Facade, Generally, Outdoor, Residence
Mounting	Surface, Wall
Connection (system)	QuickConnect



PRODUCT DATA SHEET

Dalim Up or Down 1200lm 40° 20W Dark Grey Phasecut

Art.no: 2435-40-7



Lighting Solutions

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A++ - A