

**PRODUCT DATA SHEET**

Rigil 900lm 830 360° 15W Quickconnect Dark Grey

Art.no: 2475-36-7

*Lighting Solutions*

Rigil 900lm 830 360° 15W Quickconnect Dark Grey

**A**

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK10
IP (system)	IP54
Outdoor	Yes
Operating temperature (°C)	-20 - 30

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	59
CRI / Ra (>=)	80

**PRODUCT DATA SHEET**

Rigil 900lm 830 360° 15W Quickconnect Dark Grey

Art.no: 2475-36-7

*Lighting Solutions*

PHOTOMETRIC DATA	
CCT (Color Temperature) (K)	3000
Color Code	830
Socket / Cap-Base	N/A
Lens (Diffuser)	Clear
Lifetime (h)	50 000
Forward Voltage LED (max tp=25) (V)	50.0
Driftspenning LED (min tp=65) (V)	45.0

DRIVER	
Protection Class (driver)	2
IP (driver)	IP65
Expected Lifetime (driver) (h)	30000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	250 - null
CC (forward voltage driver) (V)	36.0 - 48.0
Output Current Tolerance (%)	5.0
Current Ripple (%)	180.0
Max load pr circuit - B10	17
Max load pr circuit - B16	26
Max load pr circuit - C10	29
Max load pr circuit - C16	47
Leakage current (mA)	0.5
Inrush current time (µs)	125.0
Inrush current I _{max} (A)	15.0

DIMENSIONS	
Width (product) (mm)	120.0
Height (product) (mm)	800.0
Weight (product) (kg)	2.4

MATERIALS AND SURFACES	
Color	Antracite
RAL Code	RAL7024
Housing Material	Aluminium



PRODUCT DATA SHEET

Rigil 900lm 830 360° 15W Quickconnect Dark Grey

Art.no: 2475-36-7



Lighting Solutions

INSTALLATION AND CONNECTION	
Areas of use	Cottage, Generally, Outdoor, Residence
Mounting	Ground, Bollard
Connection (system)	QuickConnect

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A

LIGHT DISTRIBUTION

