



**PRODUCT DATA SHEET**

Atria 2000lm 830/840/857 100° 18W Ceiling mount WH

Art.no: 3010-100-3

*Lighting Solutions*

Atria 2000lm 830/840/857 100° 18W Ceiling mount WH



Comes with switch option between 3000K (default), 4000K and 5700K. QuickConnect for easy installation. All data is based on 4000K.

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK08
IP (system)	IP20
Outdoor	No

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	97

**PRODUCT DATA SHEET**

Atria 2000lm 830/840/857 100° 18W Ceiling mount WH

Art.no: 3010-100-3

*Lighting Solutions*

PHOTOMETRIC DATA	
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	3000/4000/5700
Color Code	830/840/857
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lens (Diffuser)	Opal
Lifetime (h)	L80B50: 50 000
MacAdam (SDCM)	3
Manufacturer (light source)	Everlight
Forward Voltage LED (max tp=25) (V)	75.0
Driftspenning LED (min tp=65) (V)	65.0

DRIVER	
Output Current Tolerance (%)	5.0
Current Ripple (%)	5.0
Max load pr circuit - B10	33
Max load pr circuit - B16	53
Max load pr circuit - C10	33
Max load pr circuit - C16	53
Inrush current time (μ s)	45.0
Inrush current I _{max} (A)	86.0

DIMENSIONS	
Width (product) (mm)	300.0
Height (product) (mm)	87.5
Weight (product) (kg)	1.32

MATERIALS AND SURFACES	
Color	White

INSTALLATION AND CONNECTION	
Areas of use	Generally, Hotel
Mounting	Surface, Ceiling, Pendant



PRODUCT DATA SHEET

Atria 2000lm 830/840/857 100° 18W Ceiling mount WH

Art.no: 3010-100-3



Lighting Solutions

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A++ - A

LIGHT DISTRIBUTION

