



**PRODUCT DATA SHEET**

Silla K 4750lm 830 30° 30W IP65 GR Surface

Art.no: 3920-7-30-1

*Lighting Solutions*

Silla K 4750lm 830 30° 30W IP65 GR Surface



ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP65
Outdoor	Yes

PHOTOMETRIC DATA	
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	3000
Color Code	830
Lightsource Type	LED (built in)

**PRODUCT DATA SHEET**

Silla K 4750lm 830 30° 30W IP65 GR Surface

Art.no: 3920-7-30-1

*Lighting Solutions*

PHOTOMETRIC DATA	
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	3

DRIVER	
Manufacturer (driver)	Tridonic
Protection Class (driver)	2
Max Output Voltage (V)	52
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	800 - null
CC (forward voltage driver) (V)	21.0 - 40.0
Output Current Tolerance (%)	5.0
Current Ripple (%)	5.0
Max load pr circuit - B10	21
Max load pr circuit - B16	34
Max load pr circuit - C10	42
Max load pr circuit - C16	68
Inrush current time (μ s)	250.0
Inrush current I _{max} (A)	15.0

DIMENSIONS	
Length (product) (mm)	150.0
Width (product) (mm)	150.0
Height (product) (mm)	265.0

MATERIALS AND SURFACES	
Color	Grey

INSTALLATION AND CONNECTION	
Connection (system)	Cable

ENERGY AND CERTIFICATIONS	
CE mark	Yes



PRODUCT DATA SHEET
Silla K 4750lm 830 30° 30W IP65 GR Surface
Art.no: 3920-7-30-1



Lighting Solutions

ENERGY AND CERTIFICATIONS

Energy Efficiency Class

A++ - A