

**PRODUCT DATA SHEET**

Driver 150mA cc 9W (30-60V) Phasecut AcTec JB&SM

Art.no: D15009NTF

*Lighting Solutions*

Driver 150mA cc 9W (30-60V) Phasecut AcTec JB&SM



ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	Phase-Cut
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Operating temperature (°C)	-20 - 50
Connection 1	Quickconnect
Connection 2	SM Connector

DRIVER	
Manufacturer (driver)	AcTEC

**PRODUCT DATA SHEET**

Driver 150mA cc 9W (30-60V) Phasecut AcTec JB&SM

Art.no: D15009NTF

*Lighting Solutions*

DRIVER	
Protection Class (driver)	1 or 2
Standby power P_{sb} (W) <	1.0
Flicker metric (Pst LM) <	1.0
Stroboscopic effect metric (SVM) <	0.4
Max Output Voltage (V)	60
Dimming (driver)	Phase-Cut
Dimming Phasecut Type	Leading / Trailing edge
Dimming output type	PWM
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Flicker-free	Yes
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	150 - 150
CC (forward voltage driver) (V)	30.0 - 60.0
Surge Protection	L-N = 2KV
Max load pr circuit - B16	56
Max load pr circuit - C16	118
Leakage current (mA)	5.0
Inrush current time (μ s)	100.0

DIMENSIONS	
Length (product) (mm)	109.0
Width (product) (mm)	40.0
Height (product) (mm)	22.0

MATERIALS AND SURFACES	
Color	White

ENERGY AND CERTIFICATIONS	
CE mark	Yes