

**PRODUCT DATA SHEET**

Driver 700mA cc 9W (7-13V) Phasecut AcTec SM&JB

Art.no: D70009NT-02

*Lighting Solutions*

Driver 700mA cc 9W (7-13V) Phasecut AcTec SM&JB



ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	Phase-Cut
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Connection 2	SM Connector

DRIVER	
Manufacturer (driver)	AcTEC
Protection Class (driver)	2
Max Output Voltage (V)	17

**PRODUCT DATA SHEET**

Driver 700mA cc 9W (7-13V) Phasecut AcTec SM&JB

Art.no: D70009NT-02

*Lighting Solutions*

DRIVER	
Dimming (driver)	Phase-Cut
Dimming Minimum Level (%)	1.0
Dimming Phasecut Type	Leading / Trailing edge
IP (driver)	IP20
Expected Lifetime (driver) (h)	30000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	700 - null
CC (forward voltage driver) (V)	7.0 - 13.0
Output Current Tolerance (%)	5.0
Current Ripple (%)	50.0
Max load pr circuit - B10	35
Max load pr circuit - B16	56
Max load pr circuit - C10	74
Max load pr circuit - C16	118
Leakage current (mA)	0.7
Inrush current time (μ s)	300.0
Inrush current I _{max} (A)	5.0

DIMENSIONS	
Length (product) (mm)	109.0
Width (product) (mm)	40.0
Height (product) (mm)	22.0
Weight (product) (kg)	0.07

ENERGY AND CERTIFICATIONS	
CE mark	Yes