



## PRODUCT DATA SHEET

Driver 700mA cc 30W 21-43V Phasecut AcTec JB&EPN0034

Art.no: D70030NTF-02



*Lighting Solutions*



# Driver 700mA cc 30W 21-43V Phasecut AcTec JB&EPN0034



30W phasecut driver with junctionbox on primary side.

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	Phase-Cut
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Operating temperature (°C)	-20 - 50
Connection 1	QuickConnect (L+N)
Connection 2	EPN0034 female

**PRODUCT DATA SHEET**

Driver 700mA cc 30W 21-43V Phasecut AcTec JB&amp;EPN0034

Art.no: D70030NTF-02

*Lighting Solutions*

<b>DRIVER</b>	
Manufacturer (driver)	AcTEC
Protection Class (driver)	2
Flicker metric (Pst LM) <	1.0
Stroboscopic effect metric (SVM) <	0.4
Max Output Voltage (V)	54
Dimming (driver)	Phase-Cut
Dimming Minimum Level (%)	1.0
Dimming Phasecut Type	Leading / Trailing edge
Dimming output type	Amplitude Modulation
IP (driver)	IP20
Flicker-free	Yes
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	700 - null
CC (forward voltage driver) (V)	21.0 - 43.0
Output Current Tolerance (%)	5.0
Current Ripple (%)	2.0
Max load pr circuit - B10	35
Max load pr circuit - B16	56
Max load pr circuit - C10	74
Max load pr circuit - C16	118
Max load pr circuit - C20	148
Max load pr circuit - C25	185
Leakage current (mA)	7.0
Inrush current time ( $\mu$ s)	300.0
Inrush current I <sub>max</sub> (A)	5.0

<b>DIMENSIONS</b>	
Length (product) (mm)	142.0
Width (product) (mm)	50.0
Height (product) (mm)	24.0
Weight (product) (kg)	0.2

<b>INSTALLATION AND CONNECTION</b>	
Connection (system)	QuickConnect



**PRODUCT DATA SHEET**

Driver 700mA cc 30W 21-43V Phasecut AcTec JB&EPN0034

Art.no: D70030NTF-02



*Lighting Solutions*

**ENERGY AND CERTIFICATIONS**

CE mark	Yes
---------	-----