

**FAMILY PRODUCT SHEET**

Montana L

Art.no: Montana-L

*Lighting Solutions*

Montana L



Montana feature an innovative, tool-free system that allows for easy replacement of the electrical compartment directly on-site. This ensures fast and efficient maintenance while significantly reducing labor costs and downtime. The sleek and aerodynamic design minimizes wind resistance, enhances reliability, and optimizes heat dissipation, resulting in an extended lifespan. Built to withstand challenging conditions such as Nordic roads and high-altitude environments, Montana deliver dependable performance even in extreme settings.

VARIANTS

Art.no.	Effect	Lumen out	CCT	Beam angle	Lens	CRI (>)	Dimming	Connection	Color
103050-120-BV-1	120W	16800 lm	3000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 12m	Grey
103051-120-BV-1	120W	18000 lm	3000K/4000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 12m	Grey
103052-120-BV-1	120W	16800 lm	3000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 12m	Grey
103053-120-BV-1	120W	16800 lm	3000K/ 2200KK	143°*65°	PMMA	70	DALI2, D4i	Kabel 12m	Grey
103050-120-GS-1	120W	16800 lm	3000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 12m	Grey
103051-120-GS-1	120W	18000 lm	3000K/4000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 12m	Grey
103052-120-GS-1	120W	16800 lm	3000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 12m	Grey
103053-120-GS-1	120W	16800 lm	3000K/ 2200KK	156°*54°	PMMA	70	DALI2, D4i	Kabel 12m	Grey

**FAMILY PRODUCT SHEET**

Montana L

Art.no: Montana-L

*Lighting Solutions*

Art.no.	Effect	Lumen out	CCT	Beam angle	Lens	CRI (>)	Dimming	Connection	Color
103050-150-BV-1	150W	21000 lm	3000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 14m	Grey
103051-150-BV-1	150W	22500 lm	3000K/4000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 14m	Grey
103052-150-BV-1	150W	21000 lm	3000K	143°*65°	PMMA	70	DALI2, D4i	Kabel 14m	Grey
103053-150-BV-1	150W	21000 lm	3000K/ 2200KK	143°*65°	PMMA	70	DALI2, D4i	Kabel 14m	Grey
103050-150-GS-1	150W	21000 lm	3000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 14m	Grey
103051-150-GS-1	150W	22500 lm	3000K/4000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 14m	Grey
103052-150-GS-1	150W	21000 lm	3000K	156°*54°	PMMA	70	DALI2, D4i	Kabel 14m	Grey
103053-150-GS-1	150W	21000 lm	3000K/ 2200KK	156°*54°	PMMA	70	DALI2, D4i	Kabel 14m	Grey
103050-150-IBV-1	150W	21000 lm	3000K	47.7°*83.2°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103051-150-IBV-1	150W	22500 lm	3000K/4000K	47.7°*83.2°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103052-150-IBV-1	150W	21000 lm	3000K	47.7°*83.2°	PMMA	70	DALI2, D4i	Kabel 14m	Grey
103053-150-IBV-1	150W	21000 lm	3000K/ 2200KK	47.7°*83.2°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103050-150-IBH-1	150W	21000 lm	3000K	41.9°*54°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103051-150-IBH-1	150W	22500 lm	3000K/4000K	41.9°*54°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103052-150-IBH-1	150W	21000 lm	3000K	41.9°*54°	PMMA	70	DALI2, D4i	Kabel 8m	Grey
103053-150-IBH-1	150W	21000 lm	3000K/ 2200KK	41.9°*54°	PMMA	70	DALI2, D4i	Kabel 8m	Grey