

**FAMILY PRODUCT SHEET**

LED Panel

Art.no: Panel-Base

*Lighting Solutions*

LED Panel



Panel LED is a light fixture for interior use. It is constructed for fitting in to suspended ceilings. Panel LED's can be installed as a pendant or mounted on ceiling surfaces. The Panel LED has an opal or micro prismatic diffusor. Choose between ON/OFF, Phase-Cut or DALI2 (CLO, Corridor, Push dim and Ready2mains) driver. See accessories for detailed information.

VARIANTS

Art.no.	Effect	Lumen out	CCT	Beam angle	Lens	CRI (>)	Dimming	Length	Color
0388-02-2	36W	4100 lm	3000K	110°	Micropris.	90		595.0 mm	Black
0395-01-3	36W	4573 lm	3000K	110°	Opal	80		595.0 mm	White
0396-01-3	36W	4872 lm	4000K	110°	Opal	80		595.0 mm	White
0386-2-02-3	33W	4675 lm	4000K	110°	Micropris.	80	None	595.0 mm	White
0385-2-01-3	36W	4920 lm	3000K	110°	Opal	80	None	595.0 mm	White
0385-2-02-3	36W	4563 lm	3000K	110°	Micropris.	80	None	595.0 mm	White
0386-2-01-3	33W	5250 lm	4000K	110°	Opal	80	None	595.0 mm	White
0340-4-02-3	36W	4000 lm	4000K	110°	Micropris.	80		595.0 mm	White
0331-4-02-3	36W	3590 lm	3000K	110°	Micropris.	90		595.0 mm	White
0320-4-01-3	36W	4165 lm	3000K	110°	Opal	80		1195.0 mm	White
0320-4-02-3	36W	4165 lm	3000K	110°	Micropris.	80		1195.0 mm	White

**FAMILY PRODUCT SHEET**

LED Panel

Art.no: Panel-Base

*Lighting Solutions*

Art.no.	Effect	Lumen out	CCT	Beam angle	Lens	CRI (>)	Dimming	Length	Color
0321-4-01-3	36W	4399 lm	4000K	110°	Opal	80		1195.0 mm	White
0321-4-02-3	36W	4246 lm	4000K	110°	Micropris.	80		1195.0 mm	White
0330-4-01-3	36W	3811 lm	3000K		Opal	80		595.0 mm	White
0330-4-02-3	36W	3600 lm	3000K	110°	Micropris.	80		595.0 mm	White
0340-4-01-3	36W	4100 lm	4000K	110°	Opal	80		595.0 mm	White
0370-02-3	41W	4186/4953 lm	3000/4000K	110°	Micropris.	80		595.0 mm	White
0231-02-3	24W	2693 lm	3000K		Micropris.	90		595.0 mm	White
0341-H-02-3	36W	3972 lm	4000K	90	Micropris.	90			White