



Universal G2 IP44



Universal is an elegant and splash-proof IP44 LED luminaire designed for interior and industrial use. It features easy installation with pass-through wiring, low glare, and up to 150lm/W efficiency. The luminaire comes with a DIP switch, allowing you to customize the power level as needed, and the Kelvin can be adjusted between 3000K and 4000K. Available in lengths of 600mm, 1200mm, and 1500mm in on/off, sensor (Microwave), or DALI version. This product is also available with a microwave sensor with wireless communication between luminaires, using the Norlux Wireless Connect system for control.

VARIANTS

Art.no.	Effect	Lumen out	CCT	Beam angle	Lens	CRI (>)	Dimming	Length	Color
102471-105-3	20/16/1 3/11W	2950 lm	3000/4000K	105°	Micropris.	80	None	600.0 mm	White
102471-MW-105-3	20/16/1 3/11W	2750 lm	3000/4000K	105°	Micropris.	80	None	600.0 mm	White
102471-105-3-ddd	20W	2750 lm	3000/4000K	105°	Micropris.	80			White
102472-105-3	40/35/2 9/23W	6100 lm	3000/4000K	105°	Micropris.	80	None	1200.0 mm	White
102472-MW-105-3	40/35/2 9/23W	6100 lm	3000/4000K	105°	Micropris.	80	None	1200.0 mm	White
102472-105-3-ddd	40W	6100 lm	3000/4000K	105°	Micropris.	80	DALI	1200.0 mm	White



FAMILY PRODUCT SHEET
Universal G2 IP44
Art.no: UniversalG2-IP44



Lighting Solutions

Art.no.	Effect	Lumen out	CCT	Beam angle	Lens	CRI (>)	Dimming	Length	Color
102473-105-3	47/40/3 3/26W	7300 lm	3000/4000K	105°	Micropris.	80	None	1500.0 mm	White
102473-MW-105-3	47/40/3 3/26W	7300 lm	3000/4000K	105°	Micropris.	80	None	1500.0 mm	White
102473-105-3-ddd	47W	7300 lm	3000/4000K	105°	Micropris.	80	DALI	1500.0 mm	White