

**PRODUKTDATABLAD**

Driver 24V cv 100W 1-4ch. DALI DT6 SR (TW/RGB/RGBW)

Art.no: W7101

*Lighting Solutions*

## Driver 24V cv 100W 1-4ch. DALI DT6 SR (TW/RGB/RGBW)



- Independent digital dimmable LED-driver for constant voltage 24 VDC • Supports DALI-2 specification (IEC 62386-207:2018) • Select between 1-4 addressable DALI channels • DALI-address can easily be set with integrated display (no programming needed) • Optimal for Tunable White, RGB and RGBW applications • High resolution dimming range 0.1 – 100 % • Max. output power 100 W (24 VDC)

ELEKTRISKE DATA	
Beskyttelsesklasse	2
Dimmefunksjon (system)	DALI, DALI2

TEKNISK DATA	
IP (system)	IP20
Driftstemperatur (°C)	-2 - 45

DRIVER / BALLAST	
Produsent (driver)	Welight
Produsentens driverbeskrivelse	LCV 100W 24V 1-4CH DALI SR
Effekt (driver) (W)	100
Beskyttelsesklasse (driver)	2

**PRODUKTDATABLAD**

Driver 24V cv 100W 1-4ch. DALI DT6 SR (TW/RGB/RGBW)

Art.no: W7101

*Lighting Solutions*

DRIVER / BALLAST	
Dimmefunksjon (driver)	DALI, DALI2
Minimum dimmenivå (%)	0.1
Type Dimming	PWM
Utgangsfrekvens (Hz)	500
Forventet levetid (driver) (t)	50000
Konstant strøm eller spenning (CC eller CV)	CV
Konstant spenning (CV driver) (V)	24
Strømkrusning (%)	3.0
Maks belastning per kurs - C10	16
Maks belastning per kurs - C16	26
Maks belastning per kurs - C20	32
Startstrøm I <sub>max</sub> (A)	80.0

DIMENSJONER	
Lengde (produkt) (mm)	244.0
Bredde (produkt) (mm)	32.0
Høyde (produkt) (mm)	64.0
Vekt (produkt) (kg)	0.44

MATERIALER OG OVERFLATER	
Farge	Hvit
Kapslingsmateriale	Polykarbonat