

**PRODUCT DATA SHEET**

Global Pulse Track Recessed 3-circuit 3m BK

Art.no: XTSCF6300-2

*Lighting Solutions*

## Global Pulse Track Recessed 3-circuit 3m BK



The recessed version of GLOBAL Trac Pulse for suspended ceilings. GLOBAL Trac Pulse control is a lighting track system that includes both normal input voltage and wires for transmitting the control signal to the lights. This makes it possible to use smart control systems without central units. Of these, the DALI, DMX, LON and EIB standards are the most widely known. Various manufacturers provide control units, detectors and fixtures for the control systems. All control systems share the same goal: to transmit the control signal to individual lights using the GLOBAL Trac Pulse control's wires and to create dynamic lighting.

ELECTRICAL DATA	
Voltage (system) [V]	400V 50Hz
Power (track) (kVA)	11.1
Circuits	3-circuit
Current (A)	16

TECHNICAL DATA	
Outdoor	No
Pull strength (N)	100.0

**PRODUCT DATA SHEET**

Global Pulse Track Recessed 3-circuit 3m BK

Art.no: XTSCF6300-2

*Lighting Solutions*

TECHNICAL DATA	
Track Family	Global Trac Pulse

DIMENSIONS	
Length (product) (mm)	3000.0
Width (product) (mm)	56.0
Height (product) (mm)	32.5
Weight (product) (kg)	2.92

MATERIALS AND SURFACES	
Color	Black
RAL Code	RAL9005
Housing Material	Aluminium

INSTALLATION AND CONNECTION	
Areas of use	Generally, Hotel, Museum, Restaurant, Shop, Showroom
Mounting	Recessed

ENERGY AND CERTIFICATIONS	
CE mark	Yes