

**FDV DOCUMENTATION**

Panel BL 595x595 4900lm 930/940 28W Prism IP54 WH w/o driver

Art.no: 103152-90-3

*Lighting Solutions*

Panel BL 595x595 4900lm 930/940 28W Prism IP54 WH w/o driver



SPECIFICATIONS	
Type of Dimming (system)	Depending on Driver
IK	IK02
Operating temperature (°C)	40
Color Code	930/940
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	3
Protection Class (driver)	2
Dimming (driver)	DALI2
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	1050

**FDV DOCUMENTATION**

Panel BL 595x595 4900lm 930/940 28W Prism IP54 WH w/o driver

Art.no: 103152-90-3

*Lighting Solutions*

SPECIFICATIONS	
CC (forward voltage driver) (V)	45.0
Inrush current time (μ s)	100.0
Inrush current I _{max} (A)	20.0
Length (product) (mm)	595.0
Width (product) (mm)	595.0
Height (product) (mm)	28.0
Color	White
RAL Code	RAL9016
Mounting	Recessed, Ceiling
Connection (system)	EPN0024