

**PRODUCT DATA SHEET**

Z-Flood 171000lm 1200W 740 Asymmetric F14 56° BK IP66

Art.no: 1028923-14-2

*Lighting Solutions*

Z-Flood 171000lm 1200W 740 Asymmetric F14 56° BK IP66



ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	Depending on Driver
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK08
IP (system)	IP66
Outdoor	Yes
Operating temperature (°C)	-30 - 50

PHOTOMETRIC DATA	
Lightsource Type	LED (built in)
Lifetime (h)	L90B10: 100 000

DRIVER	
Manufacturer (driver)	Up-Shine
Protection Class (driver)	1
Standby power P_{sb} (W) <	2.0
Flicker metric (P_{st} LM) <	1.0
Stroboscopic effect metric (SVM) <	0.4
Dimming (driver)	DALI2, PWM, DMX
Expected Lifetime (driver) (h)	97000
Flicker-free	Yes
Surge Protection	L/N-PE = 20KV

**PRODUCT DATA SHEET**

Z-Flood 171000lm 1200W 740 Asymmetric F14 56° BK IP66

Art.no: 1028923-14-2

*Lighting Solutions*

DRIVER	
Max load pr circuit - B10	1
Max load pr circuit - B16	2
Max load pr circuit - C10	2
Max load pr circuit - C16	2
Max load pr circuit - C20	2
Max load pr circuit - C25	3
Leakage current (mA)	0.75
Inrush current I _{max} (A)	35.0

INSTALLATION AND CONNECTION	
Areas of use	Outdoor, Sports areas
Mounting	Wall, Mast
Connection (system)	Terminal

ENERGY AND CERTIFICATIONS	
CE mark	Yes