

**PRODUCT DATA SHEET**

Uniplus 5000lm 830 90° 31W 5x2,5mm2 1200mm WH Phasecut

Art.no: 103050-90-3-p

*Lighting Solutions*

Uniplus 5000lm 830 90° 31W 5x2,5mm2 1200mm WH Phasecut



Uniplus is a surface mounted luminaire with the latest technology and optics to ensure a high luminous efficiency and low glare. -Low glare UGR<19 -Up to 150lm/W -Easy and fast installation. -Suspended installation (accessory)

ELECTRICAL DATA

Protection Class (system)	1
Dimming (system)	Phase-Cut
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA

IK (system)	IK06
IP (system)	IP40
Outdoor	No
Operating temperature (°C)	-20 - 40
Through-wiring (mm ²)	5x2,5
Nipple	Membrane M20

PHOTOMETRIC DATA

Efficacy (system) (lm/W)	130
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	3000
Color Code	830
Lightsources Type	LED (replaceable)
Lens (Diffuser)	Micropris.
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	3

**PRODUCT DATA SHEET**

Uniplus 5000lm 830 90° 31W 5x2,5mm2 1200mm WH Phasecut

Art.no: 103050-90-3-p

*Lighting Solutions*

PHOTOMETRIC DATA	
UGR (<=)	19
Manufacturer (light source)	Shenzhen leadopto Technology Co.Ltd
Forward Current LED (min-max) (mA)	0 - 150

DRIVER	
Manufacturer (driver)	AcTEC
Flicker-free	Yes

DIMENSIONS	
Length (product) (mm)	1200.0
Width (product) (mm)	162.6
Height (product) (mm)	49.5
Weight (product) (kg)	2.91

MATERIALS AND SURFACES	
Color	White
RAL Code	RAL9003
Housing Material	Metal
Diffuser Material	PMMA

INSTALLATION AND CONNECTION	
Areas of use	Generally, Industrial, Office, School, Shop
Mounting	Surface, Suspended, Ceiling
Connection (system)	Quickconnectx2

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	B
CE mark	Yes