

**PRODUCT DATA SHEET**

Driver Dali 600mA 25W 24-42V Dali 18i5/EPN0034

Art.no: 0300-2-46

*Lighting Solutions*

Driver Dali 600mA 25W 24-42V Dali 18i5/EPN0034



ELECTRICAL DATA	
Dimming (system)	DALI
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Connection 1	18i5 DALI male
Connection 2	EPN0034 female

DRIVER	
Manufacturer (driver)	Boke
Protection Class (driver)	2
Standby power P_{sb} (W) <	0.5
Flicker metric (P_{st} LM) <	1.0

**PRODUCT DATA SHEET**

Driver Dali 600mA 25W 24-42V Dali 18i5/EPN0034

Art.no: 0300-2-46

*Lighting Solutions*

DRIVER	
Stroboscopic effect metric (SVM) <	0.4
Max Output Voltage (V)	42
Dimming (driver)	DALI2
Dimming Minimum Level (%)	1.0
Dimming output type	Amplitude Modulation
IP (driver)	IP20
Expected Lifetime (driver) (h)	100000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	600 - 1050
Current setting (driver)	DIP-switch
CC (forward voltage driver) (V)	24.0 - 42.0
CV (driver) [V]	33
Output Current Tolerance (%)	5.0
Current Ripple (%)	5.0
Max load pr circuit - B10	18
Max load pr circuit - B16	29
Max load pr circuit - C10	30
Max load pr circuit - C16	48
Max load pr circuit - C20	60
Max load pr circuit - C25	75
Leakage current (mA)	0.7
Inrush current time (µs)	256.0
Inrush current I _{max} (A)	14.75

DIMENSIONS	
Length (product) (mm)	135.0
Width (product) (mm)	45.0
Height (product) (mm)	30.0

MATERIALS AND SURFACES	
Color	White

ENERGY AND CERTIFICATIONS	
CE mark	Yes



PRODUCT DATA SHEET

Driver Dali 600mA 25W 24-42V Dali 18i5/EPN0034

Art.no: 0300-2-46



Lighting Solutions